

## Richmond Hill Fire Department Self Inspection Checklist

The purpose of this form is to aid the business owner/operator in a self-evaluation of commercial property. A representative of the Richmond Hill Fire Marshal's office will follow up with an annual inspection based largely on the criteria listed below.

Exits/Means of Egress	Hazardous Materials
Exit doors unlocked & unblocked.	No open containers of flammable/combustible
Exit access unobstructed.	liquids.
Exterior of exit doors clear of obstructions.	Flammable/combustible liquids stored in approved
Exit doors & hardware fully functional.	cabinets.
Exit stairways unobstructed & free of storage.	Compressed gas cylinders secured upright.
Exit Lights fully operable.	Fuel dispensing hoses not worn or cracked.
Exit doors easily identifiable.	Cleaning supplies/chemicals stored in approved &
Emergency lighting fully operable.	labeled containers.
Emergency lighting raily operation	labeled containers.
Fire Protection Systems	<u>Electrical</u>
Fire alarm, sprinkler, and suppression systems	Outlets, switches, junction boxes have cover
inspected/tested annually (with documentation).	plates installed.
Sprinkler fire pump tested annually.	Circuit breakers/fuses labeled properly.
Wet standpipe system flow tested annually.	Openings in circuit breakers protected with
Dry standpipe system hydro-tested every 5 years.	fill plates installed.
FDC unobstructed and accessible.	Electric panel/breaker box accessible.
FDC caps in place, couplings spin freely.	
Sprinkler heads unobstructed, no storage	
within 18 inches.	<u>Housekeeping</u>
Sprinkler heads free of paint, corrosion, debris.	No accumulation of combustible waste.
Sprinkler valve room accessible, free of storage.	Electrical, mechanical, boiler rooms accessible
Fire alarm devices (pull stations, control	and free of all storage.
panels, etc.) easily accessible.	Electrical equipment and motors free of debris
Fire alarm horns/strobes operational and	and build-up (dust, lint, etc.).
unobstructed.	HVAC air filters clean and replaced regularly.
Kitchen hood system inspected and tagged	
as required.	<u>Miscellaneous</u>
Kitchen hood remote pull station accessible	Street address posted and visible from roadway.
and fully operable.	Fire hydrants on property unobstructed within
Class K fire extinguisher located within 30 feet	3 feet.
of kitchen frying equipment.	Fire lane clearly marked and unobstructed.
Fire extinguishers inspected and tagged as	Fire department access road unobstructed
required.	as required.
Fire extinguishers accessible and properly	
mounted.	
Fire Doors/Protection Assemblies	
Fire doors operable, self-closing, and latching.	
Fire doors operable, self-closing, and latering.	
Fire rated walls, floors, or ceilings not breached,	
or openings are filled with fire rated caulk.	
No obstructions interfering with operation of	
fire doors.	